



HIDROLIC
SEAL



LOCKING
SYSTEM
OPTIONAL



D400



Dimensions

ref.	model	A1 x A2	O1 x O2	H	class
920313	500	520 x 520	400 x 400	75	D400
920314	600	620 x 620	500 x 500	75	D400
920315	700	720 x 720	600 x 600	100	D400
920316	800	820 x 820	700 x 700	100	D400
920317	900	920 x 920	800 x 800	100	D400
920318	1000	1020 x 1020	900 x 900	100	D400
920319	1100	1120 x 1120	1000 x 1000	100	D400

A1 x A2 - external dimensions // O1 x O2 - clear opening // H - height

characteristics

- ductile cast iron GJS-500-7 – EN 1563;
- EN 124-2:2015, Loading class D400;
- Frame with hydraulic seal;
- Anti-slip raised pattern;
- Black painting.

place of use

Carriageway of roads (including pedestrian streets), hard shoulders and parking areas, for all types of roads vehicles (and lower groups)

Traffic

description

Square manhole cover made of ductile iron GJS-500-7 – EN 1563, breaking load > 400kN to EN 124.

Group 4 installation area - carriageway of roads (including pedestrian streets), hard shoulders and parking areas, for all types of roads vehicles (and lower groups)

opcional

- Locking system on model 500 to 800 ;
- Lifting key— ref.ª 508701

